

VesseLINK™

- Reliable satellite communications for at sea operations
- Providing 100% global coverage you can depend on
- Enabling essential communications for critical operations



VesseLINK utilizing Iridium CertusSM gives your critical marine operation global communications coverage. It is the communications solution to depend on for essential communications whenever and wherever you are at sea. Whether you operate a large fleet or a single vessel, this commercialized, military-grade solution is designed to meet your unique challenges through a simple, adaptable and robust design.

VesseLINK on Iridium operates using Iridium CertusSM broadband services over a network of 66 satellites that cover 100% of the globe, including deep oceans and the poles. The solution utilizes this robust network service to provide highly reliable, mobile and essential voice, text and web communications.

MULTI-SERVICES PLATFORM

- IP data sessions up to 700kbps(down)/352kbps (up)
- Streaming up to 256kbps
- 3 high quality voice lines
- Location tracking



21 Thornhill Drive, Dartmouth, Nova Scotia B3B 1R9 CANADA
Tel: +1 902 468-2505 | Fax: +1 902 468-4442 | Email: sales@metocean.com

metocean.com



TECHNICAL SPECIFICATIONS

Size	12 in x 9 in x 3 in (30.5 cm x 22.9 cm x 7.6 cm)
Weight	7.2 lb. (3.3 kg)
Power	12 VDC input, 11A max (7A avg.) includes powering external HGA-2 Antenna
Connectors	Front: RJ-45 LAN (3) Class 2 PoE RJ-45 WAN (1) for cellular connection RJ-14 POTS Rear: DC Power Input (10-32V) MIL-STD-1275D DC Power Input, +12V Regulated GPIO (RS-232, +12V out, DISTRESS, Radio Gateway, GPIO) TNC Connector, RF connection to Antenna Wi-Fi reverse SMA SIM slot
Mechanical	
Vibration and Shock	MIL-STD-810G, Test Method 514.6, Proc. 1, Category 20, Annex D MIL- STD-810G, Test Method 516.6,

ANTENNA SPECIFICATIONS

High-gain, electronic phased array antenna to enable the fastest upload and download speeds to cover any vessel communications need from safety services to operational reporting and logging

Size	14 in x 9 in h (35.6 cm dia. x 22.9 cm h)
Weight	6.2 lb. (2.8 kg)
Power	Directly powered by the terminal at 24 VDC
Operating	
Temperature	-30 to +55 degrees C
Mechanical Vibration and Shock	MIL-STD-810G, Test Method 514.6, Proc. 1, Category 20, Annex D MIL-STD-810G, Test Method 516.6, Proc. IV
Salt-Fog/Corrosion Standard	IEC 60945, Section Proc. IV